

MATERIAL SAFETY DATA SHEET

MAY BE USED TO COMPLY WITH OSHA'S HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200. STANDARD MUST BE CONSULTED FOR SPECIFIC REQUIREMENTS. SAFETEC OF AMERICA	HMIS HAZARD RATING			
	HEALTH	1	0 = INSIGNIFICANT	3 = HIGH
	FLAMMABILITY	0	1 = SLIGHT	4 = EXTREME
	REACTIVITY	0	2 = MODERATE	
	TRANSPORTATION INFORMATION			
PROPER SHIPPING NAME		Not regulated		
HAZARD CLASS/PKG. GRP.		None/None	REF.	Not Applicable
IDENTIFICATION NUMBER		None	LABEL	None Required

SECTION 1 - PRODUCT / COMPANY IDENTIFICATION

IDENTITY (AS USED ON LABEL AND LIST) SaniZide Plus Germicidal Solution		Page 1 of 2	
MANUFACTURER'S NAME Safetec of America, Inc.		EMERGENCY TELEPHONE NUMBER (24 Hours) (800) 255-3924	
ADDRESS (NUMBER, STREET, P.O. BOX) 887 Kensington Ave.		TELEPHONE NUMBER FOR INFORMATION (716) 895-1822	
(CITY, STATE AND ZIP CODE) Buffalo, NY 14215		DATE PREPARED September 1, 2010	
		SUPERSEDES January 27, 2009	

SECTION 2 - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

HAZARDOUS COMPONENTS (SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S))	CAS #	% (wt.) (OPTIONAL)	ACGIH TLV/TWA/STEL	
			PPM	MG/M ³
Alkyl-dimethyl-benzyl-ammonium chloride	68391-01-5	0.14	None Established	None Established
Alkyl-dimethyl-ethyl-benzyl-ammonium chloride	68956-79-6	0.14	None Established	None Established

This product is not known to contain a substance subject to Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR 372 at or above minimal amounts.

SECTION 3 - HEALTH HAZARD DATA

ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE		EMERGENCY AND FIRST AID PROCEDURES				
INHALATION: Brief (minutes) inhalation will not cause adverse effects, although, constant inhalation may cause irritation to upper respiratory tract.		Remove victim to fresh air; provide oxygen if breathing is difficult; seek medical attention if required.				
SKIN: Prolonged contact with skin may cause skin irritation.		Wash contaminated skin with mild soap and water; if irritation develops and persists, seek medical attention.				
EYES: Brief contact to liquid or vapors may cause moderate irritation; prolonged contact may cause severe irritation associated with burning and redness.		Flush eyes with clear running water for a minimum of 25 minutes while holding eyelids open; if irritation persists, seek medical attention.				
INGESTION: Ingestion of product may cause gastrointestinal irritation, nausea, vomiting and diarrhea.		DO NOT induce vomiting; seek immediate medical attention. Vomiting may be induced only under the supervision of a physician.				
HEALTH HAZARDS (ACUTE AND CHRONIC):		Acute effects are possible irritation and discomfort; no known chronic effects have been established.				
CARCINOGENICITY	NTP?	No	IARC MONOGRAPHS?	No	OSHA REGULATED?	No
No additional information						
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Preexisting skin, eye, or respiratory disorders may become aggravated through prolonged exposure.						

SECTION 4 - FIRE FIGHTING MEASURES		
FLASH POINT (METHOD USED)	FLAMMABLE LIMITS (% Volume in Air for Lowest Flashing Component)	
200°F (SETA)	LEL: Not Applicable	UEL: Not Applicable
EXTINGUISHING MEDIA		
Carbon dioxide (CO ₂), water, dry chemicals, synthetic foam. Type BC or ABC extinguishers.		
SPECIAL FIRE FIGHTING PROCEDURES		
Use self contained breathing apparatus for maximum respiratory protection. Use water spray to cool fire exposed containers and structures.		
UNUSUAL FIRE AND EXPLOSIVE HAZARDS		
Vapors can be heavier than air. Strong acids and bases react with aluminum to form hydrogen which is explosive if ignited.		

SECTION 5 - PRECAUTIONS FOR SAFE HANDLING AND USE/LEAK PROCEDURES
STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED
Provide adequate ventilation. Spills should be collected with approved inert absorbent for disposal. Use suitable disposal containers. Material collected with absorbent may be disposed of in a permitted landfill. Report per regulatory requirements.
WASTE DISPOSAL METHODS
Dispose of in accordance with Local, State, and Federal regulations. Products classified as non-hazardous may become hazardous waste upon contact with other products. Refer to "40 CFR Protection of Environment Parts 260-299" for complete waste disposal regulations. Consult your Local, State, or Federal Environmental Protection Agency before disposing of any chemicals.
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE
Keep container(s) tightly closed when not in use. Avoid inhalation of high concentration of vapors. Store in cool, dry, well ventilated area away from possible sources of ignition sources. Keep this and other chemicals out of reach of children.

SECTION 6 - EXPOSURE CONTROLS/PERSONAL PROTECTION		
RESPIRATORY PROTECTION	VENTILATION	LOCAL EXHAUST: Recommended
Ordinary, none required		MECHANICAL (GENERAL): Not required
PROTECTIVE GLOVES	EYE PROTECTION	
Use impervious gloves to prevent prolonged contact	Safety glasses recommended	
OTHER PROTECTIVE CLOTHING OR EQUIPMENT	WORK/HYGIENIC PRACTICES	
Ordinary, none required	Practice safe work habits. Use according to label instructions.	

SECTION 7 - PHYSICAL/CHEMICAL PROPERTIES	
BOILING POINT 200°F	SPECIFIC GRAVITY (WATER = 1) 1.01
VAPOR PRESSURE (mm Hg) Not determined	MELTING POINT -1.1°C
VAPOR DENSITY (AIR = 1) >1	pH (1% solution in water) 11-12
SOLUBILITY IN WATER Complete	EVAPORATION RATE (n-butyl acetate = 1) Slower than ethyl ether
APPEARANCE AND ODOR Clear liquid	VOC, US EPA (%) 0

SECTION 8 - STABILITY AND REACTIVITY		
STABILITY	UNSTABLE:	CONDITIONS TO AVOID Extreme temperatures
	STABLE: XXX	
INCOMPATIBILITIES (MATERIALS TO AVOID)		
Strong oxidizers; anionic materials		
HAZARDOUS DECOMPOSITION OR BYPRODUCTS		
Decomposition will not occur if handled/stored properly. Thermal decomposition may emit nitrous oxides, ammoniacal vapors.		
HAZARDOUS POLYMERIZATION	MAY OCCUR:	CONDITIONS TO AVOID None known
	WILL NOT OCCUR: XXX	

The information contained herein is believed to be accurate but is not warranted to be so. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed.